

better-sends-rule^{0,22}

$\forall i:\text{Id}, k:\text{Knd}, l:\text{IdLnk}, ds:x:\text{Id fp} \rightarrow \text{Type}, da:a:\text{Knd fp} \rightarrow \text{Type},$
 $f:(tg:\text{Id} \times (\text{State}(ds) \rightarrow \text{Valtype}(da;k) \rightarrow (da(\text{recv}(l,tg))?\text{Void List}))) \text{ List}.$
 $\text{source}(l) = i$
 $\Rightarrow @i:$ with declarations
 $ds:ds$
 $da:da$
 $k(v)$ sends f s v on link l
realizes es .
 $(\forall x:\text{Id. vartype}(i;x) \subseteq \rho \ ds(x)?\text{Top})$
& $(\forall e:\text{E. loc}(e) = i \in \text{Id} \Rightarrow \text{valtype}(e) \subseteq \rho \ \text{Valtype}(da;\text{kind}(e)))$
& $(\forall e:\text{E. isrcv}(e) \Rightarrow \text{lnk}(e) = l \in \text{IdLnk} \Rightarrow \text{valtype}(e) \subseteq \rho \ \text{Valtype}(da;\text{kind}(e)))$
& $(\forall e:\text{E.}$
 $\text{loc}(e) = i \in \text{Id}$
 $\Rightarrow \text{kind}(e) = k \in \text{Knd}$
 $\Rightarrow (\exists L;\{e':\text{E} | \text{isrcv}(e') \& \text{lnk}(e') = l \in \text{IdLnk}\} \text{ List}.$
 $(\forall e':\text{E. } (e' \in L) \Leftrightarrow \text{isrcv}(e') \& \text{lnk}(e') = l \in \text{IdLnk} \& \text{sender}(e') = e \in \text{E})$
& $(\forall e_1, e_2:\text{E. } e_1 \text{ before } e_2 \in L \Rightarrow (e_1 <_{\text{loc}} e_2))$
& $\& \text{map}(\lambda e'.\langle \text{tag}(e'), \text{val}(e') \rangle; L)$
=
tagged-list-messages($\lambda z.z$ when $e;\text{val}(e);f$)
 $\in (tg:\text{Id} \times \text{Valtype}(da;\text{recv}(l,tg))) \text{ List})$