

ecl-mng-sends-single^{0,22}

$\forall i:\text{Id}, ds:x:\text{Id} \text{ fp} \rightarrow \text{Type}, da:k:\text{Knd} \text{ fp} \rightarrow \text{Type}, A:\text{ecl}(ds;da), k:\text{Knd}, l:\text{IdLnk}, tg:\text{Id}, n:\mathbb{N}, f:(\text{State}(ds) \rightarrow \text{Valtype}(da;k) \rightarrow da(\text{rcv}(l,tg))?\text{Void}), es:\text{ES}.$
 $\text{source}(l) = i$
 $\Rightarrow (@i[[A;k \text{ sends on } l \text{ with tag } tg [s,v.f(s,v)], \text{ at marker } n]])$
 \Leftrightarrow
 $(\text{es-decls}(es;i;ds;da))$
 $\Rightarrow \text{with decls } ds$
 da
 $\text{sends on } l \text{ from } e$
 $\text{include if } \text{kind}(e) = k \wedge_2 \text{action}[[A\ n]][\text{es-init}(es;e);e] \rightarrow$
 $\quad [\langle tg, f((\text{state when } e), \text{val}(e)))]$
 $\quad \text{else nil fi}$
 $\text{and only these for tags in } [tg]))$