

## **es-sends-iff\_functionality<sup>11,40</sup>**

$\forall es:\text{event\_system}\{\text{i:l}\}, l:\text{IdLnk}, tgs:(\text{Id List}), da:\text{fpf(Knd; k.Type)},$   
 $f_1, f_2:(\{e:\text{es-E}(es)| \text{loc}(e) = \text{source}(l) \in \text{Id}\} \rightarrow ((tg:\text{Id}$   
 $\times \text{fpf-cap}(da; \text{Kind-deq; rcv}(l, tg); \text{void}) \text{ List}))$ ,  
 $ds_1, ds_2:\text{fpf(Id; x.Type)}.$   
 $\text{fpf-sub(Id; x.Type; id-deq; } ds_2; ds_1)$   
 $\Rightarrow (\forall e:\{e:\text{es-E}(es)| \text{loc}(e) = \text{source}(l) \in \text{Id}\} . f_1(e) = f_2(e))$   
 $\Rightarrow \text{with decls } ds_1 \text{ dasends on } l \text{ from } e \text{ include } f_1(e) \text{ and only these for tags in } tgs$   
 $\Rightarrow \text{with decls } ds_2 \text{ dasends on } l \text{ from } e \text{ include } f_2(e) \text{ and only these for tags in } tgs$